



Hikvision DS-QAZ0530G1

· Specification summary



Impedance	8 Ω
Rated Audio Power	30 W
Total Harmonic Distortion (THD)	$\leq 1\%$
Sensitivity (1 m, 1 W)	92 dB
Max. Acoustic Pressure (1 m)	104 dB SPL at 1 m
Frequency Response	80 Hz to 20 kHz (-10 dB)
Speaker Unit	1 $\times$ 1.0-inch tweeter and 1 $\times$ 6.5-inch woofer
Audio In	Constant voltage input: 100 V/Constant voltage input: 70 V/Constant impedance input: 8 Ω
Power Taps	100 V: 30/15/7.5 W; 70 V: 30/15/7.5/3.25 W; 8 Ω input
Material	Main body: PC Base: ABS
Dimension	$\varnothing 286.74\text{mm} \times 246.17\text{mm}$ (11.29" $\times$ 9.69")
Weight	Approx. 2.7 kg (5.95 lb.)
Package Dimension	350 mm $\times$ 350 mm $\times$ 343 mm (13.78" $\times$ 13.78" $\times$ 13.5")
With Package Weight	Approx. 2.9 kg
Packing List	Device $\times$ 1 Regulatory Compliance and Safety Information $\times$ 1
Operating Temperature	-10 $^{\circ}\text{C}$ to 45 $^{\circ}\text{C}$
Operating Humidity	$\square 90\%$ (No condensation)

Specifications are summarised from the manufacturer's published information (checked 2026-09-10). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-accessory-ds-qaz0530g1.html>