



Hikvision DS-QAZ0610G1

· Specification summary

Impedance	8 Ω
Rated Audio Power	10 W
Total Harmonic Distortion (THD)	$\leq 1\%$
Sensitivity (1 m, 1 W)	89 dB
Max. Acoustic Pressure (1 m)	98 dB SPL at 1 m
Frequency Response	120 Hz to 20 kHz (-10 dB)
Speaker Unit	1 $\times$ 1.0-inch tweeter and 1 $\times$ 6.5-inch woofer
Coverage Angle	Conical Coverage: 88°
Audio In	Constant voltage input: 100 V/Constant voltage input: 70 V/Constant impedance input: 8 Ω
Power Taps	100 V: 10/5/2.5 W; 70 V: 10/5/2.5/1.25 W; 8 Ω input
Material	Main body: PC Base: ABS
Dimension	$\varnothing 242.78$ mm $\times$ 192.7 mm (9.56" $\times$ 7.59")
Weight	Approx. 2.7 kg (5.95 lb.)
Language Support	5 languages: English, French, Spanish, German, Italian
Package Dimension	305 mm $\times$ 305 mm $\times$ 315 mm (12.01" $\times$ 12.01" $\times$ 12.4")
With Package Weight	Approx. 2.9 kg
Packing List	Device $\times$ 1 Regulatory Compliance and Safety Information $\times$ 1
Operating Temperature	-10 $^{\circ}$ C to 45 $^{\circ}$ C
Operating Humidity	$\square 90\%$ (No condensation)

Specifications are summarised from the manufacturer's published information (checked 2026-09-10). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-accessory-ds-qaz0610g1.html>