



Hikvision DS-TCG406-E(S)(12V/PoE) (2812)(O-STD)

4MP Entrance & Exit ANPR camera · Specification summary



Key features

Multi-frame ANPR & deep-learning algorithm, Supports recognition of dirty license plates, vehicle types, colors, and brands, ANPR Capture rate >98%, Vehicle moving direction recognition accuracy > 96%, Mistaken capture rate <2% (entrance/exit), <5% (checkpoint); 1/1.8" progressive CMOS; Up to 2688x1520@25fps, H.265, Min. illumination Color: 0.0005Lux@F1.2; 2.8-12mm motorized VF Lens; 4 built-in high-performance LEDs (integrated White Light & IR); Support relay output to control barrier gate, Supports multiple trigger modes, such as video detection, I/O coil, radar mixed traffic, etc; 1 TF card slot, up to 1TB, PoE/12VDC, IP67, IK10

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-hikvision-barrier-ds-tcg406-e.html>