



Hikvision DS-TMG035 (Anti-fall)

DS-TMG035 entrance and exit radar, anti-fall variant listed by manufacturer · Specification summary

Working voltage in cited document	9 to 12 VDC
Response time in cited document	50 ms
Dimensions in cited document	96 × 60 × 29 mm
Dimensions (L × W × H)	96 × 60 × 29 mm
Working temperature	-40°C~+85°C
Working voltage (VDC)	9 to 12 VDC
Working current (A)	□ 0.25A
Consumption (W)	□ 3W
Transmitting frequency (GHz)	60/79GHz
Transmitting power (mW)	≤ 10mW
Beam width	Vertical 10°, Horizontal 38°
Response time (ms)	50ms
Trigger distance (m)	0.3 to 6 m (adjustable)
Detection area (m)	Horizontal width: 0 to 2 m (adjustable)
Detection target	Vehicle
Area vehicle following	Distinguish following distance of vehicle: 0.5 to 2 m (adjustable)
Online debugging	Serial port/Wi-Fi
Online upgrade	Serial port upgrade
Weight	<350 g (0.80 lb)

Specifications are summarised from the manufacturer's published information (checked 2026-10-07). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-hikvision-barrier-radar-ds-tmg035-anti-fall.html>