



Hikvision DS-TVL224-4-5Y

· Specification summary



Maintenance Mode	Front
Pixel Pitch	P4.75
Resolution	64 × 64
Display Content	GB2312 Character Set,16*16 Lattice Chinese Characters
Screen Type	LED
Display Color	Red, Green, Yellow
Number of Module	2
Viewing Angle	120° (H) / 120° (V)
Display Mode	instant,left shift,up forward,etc.
Pixel Pitch Category	4.75
Color Temperature	3000 K to 6000 K
Brightness Uniformity	≥95%
Color Uniformity	≥95%
Contrast Ratio	2000 : 1
Luminance	3500 cd/m ²
Scanning Mode	8S
Communication Mode	TCP
Screen Border Material	Iron Frame Spraying Plastic(Dark armored glass for display part)
Working Temperature and Humidity	-30 to 60 °C 10% to 85% RH
Supply frequency	50/60 Hz
Maximum input current	0.5 A
Package Dimensions	470 × 615 × 200 mm
Dimensions	355 × 495 × 80 mm
Weight	8 kg (17.64 lb.)
Weight (with Package)	9.6 kg (21.16 lb.)
Storage Temperature and Humidity	-40 to 70 °C 10% to 85% RH

Average Consumption	20 W
Max. Consumption	70 W
Lifespan	100000 hours
Protection	IP54
Display application	Parking-space availability, license plates, welcome messages and time
Additional character support	Standard English, numeric and other foreign special characters
Content control	Control computer defines displayed content
Communication interface	RJ45; online and offline modes

Specifications are summarised from the manufacturer's published information (checked 2026-09-10). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hikvision-accessory-ds-tvl224-4-5y.html>