Hikvision DS-UPS1000-R/UK/UNI(E)

Uninterruptible Power Supply · Specification summary



Product Category	UPS
Operating Temperature	0°C to 40°C
Operating Humidity	0% to 90% non-condensing
Dimensions	276.1 × 101 × 142 mm
Approximate Weight	4.76 kg for UK universal-outlet variant
Regional Variant	UK universal outlet
UPS Capacity	1000 VA / 600 W
Input Voltage Range	DS-UPS1000-R: 140 VAC to 290 VAC DS-UPS1000-R(□□□□)/□□/□□□(E),DS-UPS1000-R(□□□□)/□□/□□□ (E):140 VAC to 300 VAC DS-UPS1000-R(□□□□)/□□/□□:162 VAC to 268 VAC (220V) 170 VAC to 280 VAC (230V) 177 VAC to 290 VAC (240V)
Input Frequency	50/60 Hz self-adaptive
Plug Type	DS-UPS1000-R(□□□□)/□□/□□□(E):UK TYPE G DS-UPS1000-R(□□□□)/□□/□□□(E),DS-UPS1000-R(□□□□)/□□/□ □:Schuko
Output Voltage Range	DS-UPS1000-R:210 VAC to 235 VAC DS-UPS1000-R(□□□□)/□□/□□:220/230VAC ± 10% DS-UPS1000-R(□□□□)/□□/□□□(E),DS-UPS1000-R(□□□□)/□□/□□□ (E):230VAC ± 10%
Output Frequency	50/60 Hz ± 0.5 Hz self-adaptive
Transfer Time	≤ 10 ms
Waveform	PWM
Outlet Type	DS-UPS1000-R(□□□□)/□□/□□□(E),DS-UPS1000-R(□□□□)/□□/□□□ (E):Universal DS-UPS1000-R(□□□□)/□□/□□:Schuko
Battery Type	12 V/9 Ah x 1, lead-acid battery
Recharge Time	4-6 hours recover to 90% capacity
Typical Backup Time	Run time at 100w: 20-25 min
Communicate Ports	No
Full Protection	Surge protection, Overload protection, Discharge protection, Short circuit protection
Display	LED indicator Line mode: Solid green led lighting Battery mode: Solid yellow led flash Fault mode: Solid red led lighting

Alarm	Charging Mode (DC mode): Sounding every 8 seconds Low Battery: Sounding every second Overloading Mode: Sounding every 0.5 seconds Fault: Continuously sounding
Dimension	276.1 mm × 101 mm × 142 mm (10.9" × 3.98" × 5.59")
Weight	DS-UPS1000-R:Approx. 5.4 kg (11.9 lb) DS-UPS1000-R(□□□□)/□□/□□:Approx. 5.55 kg (12.24 lb) DS-UPS1000-R(□□□□)/□□/□□□(E),DS-UPS1000-R(□□□□)/□□/□□□ (E):Approx. 4.76 kg (10.5 lb)

Specifications are summarised from the manufacturer's published information (checked 2026-10-25). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-hikvision-accessory-ds-ups1000-r-uk-uni-e.html