Hikvision DS-VE11-R/HW1(E2434/6325P)



Single-socket Rackmount Server · Specification summary

CPU	E-2434 (3.4 GHz-5.0 GHz, 12 MB Cache, 4 Cores, 8 Threads) / 6325P (3.5 GHz-5.2 GHz, 12 MB Cache, 4 Cores, 8 Threads)
Memory	16GB DDR5×1
Memory Slots	4 x DDR5 DIMM slots, supports UDIMM 4 × 32 GB MAX
Hard Disks	2T 7.2K SATA×2(RAID_1)
Drive Slots	4 × 3.5-inch SAS/SATA (HDD/SSD) slots
Storage Controller	S160 Chipset with OS software Raid (support RAID 0/1)
PCIe Slots	Up to 2 PCIe Gen4 slots on the Gen4 Riser
Remote Manage	iDrac9 Enterprise
Ethernet Port	2× LAN10/100/1000
Form Factor	1U Rack
Power Supply	600 W, 50/60 Hz, 100-240 VAC (Auto adjustment), 7.1-3.6 A
Dimension (W × H × D)	482.0 mm × 42.8 mm × 598.9 mm
Operating Temperature	10 °C to 35 °C (50 °F to 95 °F)

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-hikvision-network-ds-ve11-r-hw1-e2434-6325p.html