Hikvision IDS-2CD7546G0-IZHS(Y)(R)

4MP DeepinView Outdoor Moto Varifocal Dome Camera · Specification summary



Image Sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	2688 × 1520
Min. Illumination	Color: 0.0005 Lux @ (F1.2, AGC ON), B/W: 0.0001 Lux @ (F1.2, AGC ON), 0 Lux with IR
Focal Length	2.8 to 12 mm (horizontal FOV 114.5° to 41.8°) or 8 to 32 mm (horizontal FOV 42.5° to 15.1°)
Iris Type	P-iris
Supplement Light Range	2.8 to 12 mm: 30 m, 8 to 32 mm: 50 m
Video Compression	Main stream: H.265+/H.265/H.264+/H.264
Video Bit Rate	32 Kbps to 8 Mbps
Ethernet Interface	1 RJ45 10 M/100 M/1000 M self-adaptive Ethernet port
On-Board Storage	Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 1 TB
Protection	IP67: IEC 60529-2013, IK10: IEC 62262:2002
Power	12 VDC ± 20%, 1.23 A, max. 14.7 W / 24 VAC ± 20%, 0.91 A, max. 13.7 W / PoE: IEEE 802.3at, Type 2, Class 4, max. 15.0 W
Startup and Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F)
Dimension	Ø162 mm × 141.8 mm

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·
https://www.isdsb.com.my/product-hikvision-camera-ids-2cd7546g0-izhs-y-r.html