HiLook IPC-B120HA-LU

2 MP Smart Hybrid Light MD 2.0 Fixed Bullet Network Camera · Specification summary



Image Sensor	1/2.9" Progressive Scan CMOS
Max. Resolution	1920 × 1080
Min. Illumination	Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Lens Type	Fixed focal lens, 2.8 and 4 mm optional
Supplement Light	IR, White Light, up to 30 m
Video Compression	Main stream: H.265+/H.265/H.264+/H.264, Sub-stream: H.265/H.264/MJPEG
Wide Dynamic Range (WDR)	Digital WDR
Built-in Microphone	Yes
Ethernet Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
Protection	IP67: IEC 60529-2013
Power	12 VDC ± 25%, 0.4 A, max. 5 W / PoE: IEEE 802.3af, Class 3, max. 6.5 W
Dimension	184.1 mm × 66 mm × 69.1 mm

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-hilook-camera-ipc-b120ha-lu.html