



HiLook IPC-B640H-Z

· Specification summary

Device class	Motorized varifocal network bullet camera
Maximum image resolution	Up to 4 MP in the cited card; this does not specify a full-resolution frame rate or guarantee identification distance.
Lens selection	2.8 to 12 mm motorized varifocal lens; motorized lens adjustment is not pan/tilt PTZ movement.
Video compression	H.265+, H.265, H.264+ and H.264 are listed; confirm camera stream, firmware and recorder compatibility.
Night illumination	Infrared illumination up to 30 m in the cited card; this is not guaranteed identification distance.
Ingress protection	IP67 reference for the cited camera configuration; not approval for continuous immersion, unsuitable joints or an unspecified installation.
Dynamic range	120 dB WDR reference in the cited card; actual scene performance depends on configuration.
Power arrangement	PoE support is listed; confirm the actual IEEE standard, voltage, power budget and compatible power source before supply.
Local storage reference	TF card slot is listed; capacity and card compatibility need checking, and no memory card is included by this reference.

Specifications are summarised from the manufacturer's published information (checked 2026-10-20). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-hilook-ip-analog-camera-ipc-b640h-z-hilook-ipc-b640h-z-4mp-motorized-bullet.html>