



HiLook NS-0105D

· Specification summary

Ethernet ports	5 RJ45 ports at 10/100 Mbps; these are Fast Ethernet, not Gigabit ports.
Switching capacity	1 Gbps aggregate reference; not an individual port link speed.
Packet forwarding rate	0.74 Mpps manufacturer reference; not a per-port bitrate.
MAC address table	2 K as printed; not the number of physical ports or a guaranteed device count.
Internal cache	0.768 Mbits; not megabytes or video recording capacity.
Forwarding method	Store-and-forward switching.
MAC learning	MAC address auto-learning and aging are listed.
Indicators	LINK/ACT indicates port activity; PWR indicates device power. Indicators do not prove that a remote service is working.
Enclosure	ABS shell reference; not a metal enclosure claim.
Input supply	5 V DC, 0.6 A input reference; confirm the actual power adapter before connection.
Operating temperature	0 to 40 °C in the exact-model table.
Storage temperature	-40 to 85 °C; storage only, not the operating range.
Operating humidity	5% to 95%, non-condensing.
Net weight reference	0.093 kg as printed in this exact-model table; verify the actual supplied assembly and revision.
Mounting reference	Desktop and wall-mounting references are listed; confirm fixings, orientation and clearance separately.

Specifications are summarised from the manufacturer's published information (checked 2026-10-20). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-hilook-network-switch-transmission-n-s-0105d-hilook-ns-0105d-5-port-gigabit-switch.html>