



HiLook NVR-104MH-D/W

· Specification summary

IP Video Input	4-ch
Incoming/outgoing bandwidth	50/40 Mbps
HDMI/VGA output	1-ch, resolution: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Audio Output	1-ch, RCA (linear, 1 KΩ)
Recording resolution	4 M/3 M/1080p/1.3 M/720p
Synchronous Playback	4-ch
Decoding capacity	2-ch@1080p / 1-ch@4 MP
SATA	1 SATA interface
HDD capacity	Up to 6 TB capacity for each disk
Frequency band	2.4 GHz
Antenna structure	2 × 2MIMO
Transmission speed	144 Mbps
Transmission standard	IEEE 802.11b/g/n
Wireless client capacity	Up to 16 terminals, including phones and laptops, may access the NVR over Wi-Fi.
Network Interface	1, RJ45 10/100 Mbps Ethernet interface
USB Interface	Rear panel: 2 × USB 2.0
Power Supply	12 VDC
Consumption (without HDDs)	≤ 12 W
Working Temperature	-10 °C to +55 °C
Working Humidity	10% to 90%
Dimensions (W × D × H)	260 × 246 × 48 mm
Weight (without HDDs)	≤ 1 kg
Video Compression	H.264, H.265, H.264+ and H.265+.
VCA event support	Line crossing and intrusion VCA events for IP cameras.
Smart search	Supported
Client application	HiLookVision

Specifications are summarised from the manufacturer's published information (checked 2026-09-10). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-hilook-nvr-dvr-nvr-104mh-d.html>