



Huawei S110-16LP2SR

Ethernet Switch · Specification summary



Huawei description	16 x 10/100/1000BASE-T ports, 2 x GE SFP ports PoE+ Packet forwarding rate: 26.78 Mpps Switching capacity: 36 Gbit/s
Part number	98012197
Huawei category	Switch / S110 Series
Installation type	Rack mounting,Desk mounting,Wall mounting
Maximum PoE power consumption [W]	124
GE RJ45	16 (PoE+) (1G/100M/10M)
Packet forwarding rate	26.78 Mpps
Switching capacity	36 Gbit/s
Dimensions with packaging (H x W x D) [mm(in.)]	90.0 mm x 555.0 mm x 400.0 mm (3.54 in. x 21.85 in. x 15.75 in.)
Dimensions without packaging (H x W x D) [mm(in.)]	Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 260.0 mm (1.72 in. x 17.40 in. x 10.24 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 267.0 mm (1.72 in. x 17.40 in. x 10.51 in.)
Input voltage range [V]	AC input: 90 V AC to 300 V AC; 47 Hz to 63 Hz
Power supply mode	AC built-in
Maximum power consumption [W]	Without PoE: 22.0 W Full PoE load: 160.0 W (PoE: 124 W)
Weight with packaging [kg(lb)]	3.7 kg (8.16 lb)
Weight without packaging [kg(lb)]	3.0 kg (6.61 lb)

Specifications are summarised from the manufacturer's published information (checked 2026-10-27). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-huawei-network-s110-16lp2sr.html>