Panasonic PM-PB6ULVR-W

6MP Varifocal Bullet Network Camera



Specifications compiled by IS Distributions from the Panasonic official datasheet. Confirm the exact model, version and suffix before ordering. Supply, price, availability and local terms are confirmed separately by ISD.

Product type	6MP Varifocal Bullet Network Camera
Series	P-Series
Sensor	1/2.5" CMOS
Resolution	6MP (3296×1856)
Frame rate	1-30 fps (60Hz) / 1-25 fps (50Hz)
Compression	H.265+, H.265, H.264+, H.264 (sub/third stream MJPEG)
Lens	2.8-12mm motorised varifocal, F1.6, 4.3x zoom
FOV	H108°-36° V57°-20° D129°-42°
IR range	50-70 m
Min illumination	0.008 lux colour (F1.6)
WDR	120 dB
Analytics	line crossing, region intrusion, entrance/exiting, abandoned/missing object, loitering, illegal parking, target counting, heat map, face detection/recognition (with NVR)
Network	RJ45 10/100M; ONVIF Profile S/G/M/T
Power	DC 12 V or PoE (IEEE 802.3af/at), under 11.5 W
Protection	IP67
Operating temp	-30 to 60 °C
Dimensions	272.3 x 94.9 x 88.9 mm
Weight	approx. 1.04 kg
Certifications	EN 55032/55035, EN IEC 62368-1, RoHS, NDAA