Panasonic PM-VP4ULVR-W

4MP PTZ IP Camera

Specifications compiled by IS Distributions from the Panasonic official datasheet. Confirm the exact model, version and suffix before ordering. Supply, price, availability and local terms are confirmed separately by ISD.

Product type	4MP PTZ IP Camera
Series	V-Series
Sensor	1/2.7" BSI CMOS
Resolution	4MP (2560x1440)
Frame rate	30 fps (60Hz) / 25 fps (50Hz)
Compression	H.265+, H.265, H.264+, H.264, MJPEG
Lens	f=4.8-120mm, F1.65-F3.8, 25x optical zoom
Pan / tilt	pan 360° endless, tilt -10° to 90°
IR range	160 m
Min illumination	0.01 lux colour, 0.002 lux B/W, 0 lux with IR
WDR	120 dB
Analytics	face capture, vehicle detection/tracking, tripwire, intrusion, region entry/exit, human/vehicle tracking, motion
Network	RJ45 10/100M; ONVIF Profile S/G/T
Power	DC 12 V ±25% or PoE+ (IEEE 802.3at), max 23 W
Protection	IP66, IK10 (excluding glass)
Operating temp	-40 to 60 °C
Dimensions	Ø173 x 268 mm
Weight	approx. 2.1 kg
Certifications	EN 55032/55035, EN IEC 62368-1, RoHS, NDAA