Panasonic PM-VT6ULVC-W

6MP Varifocal Turret Full Colour Camera



Specifications compiled by IS Distributions from the Panasonic official datasheet. Confirm the exact model, version and suffix before ordering. Supply, price, availability and local terms are confirmed separately by ISD.

Product type	6MP Varifocal Turret Full Colour Camera
Series	V-Series
Sensor	1/2.5" CMOS
Resolution	6MP (3200×1800)
Frame rate	20 fps at 6MP; 30 fps (60Hz) / 25 fps (50Hz) at 4MP/1080P
Compression	H.265+, H.265, H.264+, H.264 (sub/third stream MJPEG)
Lens	2.8-12mm motorised varifocal, F1.6, 4.3x zoom
FOV	H108°-36° V57°-20° D129°-42°
IR / white light	30-50 m / 30-40 m
Min illumination	0.008 lux @F1.6
WDR	120 dB
Analytics	line crossing, region intrusion (human/vehicle/non-motor), abandoned/missing object, SMD
Network	RJ45 10/100M; ONVIF
Power	DC 12 V or PoE (IEEE 802.3af), under 9.5 W
Protection	IP67
Operating temp	-30 to 60 °C
Dimensions	Ø111.6 x 99.6 mm
Weight	approx. 0.66 kg
Certifications	EN 55032/55035, EN IEC 62368-1, RoHS, NDAA