



Ruijie RG-NBS3200-24GT4XS-P-V2

24-Port Gigabit Layer 2+ Cloud Managed PoE Switch · Specification summary



Ruijie description	24-Port Gigabit Layer 2+ Cloud Managed PoE Switch, 4 x 10G Uplinks
Product Category	Layer 2+
Total number of RJ45 ports	24
Total number of optical ports	4
Number of 10GE SFP+ ports	4
Number of 10/100/1000BASE-T ports	24
Number of PoE Out ports	24
Number of PoE/PoE+ Out ports	24
PoE budget	370 W
PoE power pins	1-2 (+), 3-6 (-)
Forwarding rate	96 Mpps
Switching capacity	128 Gbps(bit/s)
MTBF	400,000 hours
Operating temperature	0°C to +50°C (32°F to 122°F)
Altitude	Operating altitude: 0 m to +5,000 m (0 ft. to +16,404.20 ft.); Storage altitude: 0 m to +5,000 m (0 ft. to +16,404.20 ft.)
Surge protection	Service port: ±6 kV for common mode; Power connector: ±6 kV for both common mode and differential mode
PoE watchdog	Yes
Jumbo frame length (MTU)	9216 bytes (interface configuration mode)
Port isolation	Yes
Broadcast storm control	Yes

Specifications are summarised from the manufacturer's published information (checked 2026-10-27). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-ruijie-network-rg-nbs3200-24gt4xs-p-v2.html>