



Ruijie RG-NBS3200-24SFP/8GT4XS

24-Port Gigabit SFP with 8 combo RJ45 ports Layer 2+ Managed Fiber Switch · Specification summary



Product Category	Layer 2+
Total number of RJ45 ports	8 (including eight combo ports)
Total number of optical ports	28 (including eight combo ports)
Number of 1GE combo ports	8
Number of 1GE SFP ports	24 (including eight combo ports)
Number of 10GE SFP+ ports	4
Number of 10/100/1000BASE-T ports	8 (including eight combo ports)
Forwarding rate	95.23 Mpps
Switching capacity	128 Gbps(bit/s)
MTBF	400,000 hours
Operating temperature	0°C to +50°C (32°F to 122°F)
Altitude	Operating altitude: -500 m to +5,000 m (-1,640.42 ft. to +16,404.20 ft.); Storage altitude: -500 m to +5,000 m (-1,640.42 ft. to +16,404.20 ft.)
Surge protection	Service port: ±6 kV for common mode; Power connector: ±6 kV for both common mode and differential mode
PoE watchdog	No
Jumbo frame length (MTU)	9216 bytes (interface configuration mode)
Port isolation	Yes
Broadcast storm control	Yes

Specifications are summarised from the manufacturer's published information (checked 2026-10-27). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-ruijie-network-rg-nbs3200-24sfp-8gt4xs.html>