ST FS3388

Cable Management Rack · Specification summary



Rack units	33U
Width	800 mm
Depth	800 mm
Height	1630 mm
Door option suffix	P = perforated front door, A = acrylic transparent front door
Front door	Twin front perforated or acrylic transparent door with flush lockset
Rear door	Twin rear perforated door with flush lockset
Side panels	2 detachable quick-release side panels with latch and lockset
Base	Castor wheels with front braking system and adjustable feet
Cross members	6
Panel mounting members	4 adjustable 19-inch 1.5 mm panel mounting members (PMM)
Cable management	4 sets side vertical cable management panels with cover
Power distribution	Vertical PDU with 10 × 13A SSO power outlets, 20A MCB protector, cable and 3-pin plug
Ventilation	2 × AC 240V ventilation fans
Equipment trays	2
Cage nuts	40 sets M6 cage nut and screw
Finish	Epoxy powder coating, texture black (CC9005)

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-st-rack-fs3388.html