# ST NR33810

NetworkR Cable Management Server Rack · Specification summary



| | |
|---|---|
| **Rack units** | 33U |
| **Width** | 800 mm |
| **Depth** | 1000 mm |
| **Height** | 1684 mm |
| **Door option suffix** | P = perforated front door, A = acrylic transparent front door |
| **Front door** | Twin front perforated or acrylic transparent door with flush lockset |
| **Rear door** | Twin rear perforated door with flush lockset |
| **Side panels** | 2 detachable quick-release side panels with latch and lockset |
| **Base** | Heavy-duty castor wheels with front braking system and adjustable feet |
| **Cross members** | 8 |
| **Panel mounting members** | 4 adjustable 19-inch 2.0 mm panel mounting members (PMM) with U marking |
| **Cable management** | 4 sets side vertical cable management panels with cover |
| **Power distribution** | Vertical PDU with 10 × 13A SSO power outlets, 20A MCB protector, cable and 3-pin plug |
| **Ventilation** | 2 × AC 240V ventilation fans |
| **Equipment trays** | 2 |
| **Cage nuts** | 40 sets M6 cage nut and screw |
| **Finish** | Epoxy powder coating, texture black (CC9005) |
| **Load rating (ST catalogue)** | 1000 kg SWL |
| **Standards (ST catalogue)** | EIA-310-D; IEC 297-2; DIN 41494 part 7; 1U = 44.45 mm |
| **ST catalogue code** | networkR1000-33 |

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-st-rack-nr33810.html