ST SR2868

ServerR Floor Standing Server Rack · Specification summary



Rack units	28U
Width	600 mm
Depth	800 mm
Height	1462 mm
Door option suffix	P = perforated front door, A = acrylic transparent front door
Front door	Single front perforated or acrylic transparent door with flush lockset
Rear door	Twin rear perforated door with flush lockset
Side panels	2 detachable quick-release side panels with latch and lockset
Base	Heavy-duty castor wheels with front braking system and adjustable feet
Cross members	8
Panel mounting members	4 adjustable 19-inch 2.0 mm panel mounting members (PMM) with U marking
Power distribution	Vertical PDU with 10 × 13A SSO power outlets, 20A MCB protector, cable and 3-pin plug
Ventilation	2 × AC 240V ventilation fans
Equipment trays	2
Cage nuts	40 sets M6 cage nut and screw
Finish	Epoxy powder coating, texture black (CC9005)
Load rating (ST catalogue)	1000 kg SWL
Standards (ST catalogue)	EIA-310-D; IEC 297-2; DIN 41494 part 7; 1U = 44.45 mm
ST catalogue code	serverR800-28

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-st-rack-sr2868.html