TP-Link FC111B-20

Omada 10/100 Mbps WDM Media Converter · Specification summary



Standards and Protocols	IEEE802.3, IEEE802.3i, IEEE802.3u
Interface	1× 100 Mbps SC/UPC Fiber Port; 1× 10/100 Mbps RJ45 Port (Auto MDI/MDIX)
Network Media	Single-mode Fiber (9/125μm, maximum 20km); 100BASE-Tx: 2-pair UTP/STP of Cat. 5 or above (maximum 100 m)
Power Supply	External Power Adapter: 5 V/0.6 A
LED	PWR, Link/Act
Wave Length	1310 nm TX, 1550 nm RX
Dimensions (W × D × H)	94.5*73*27 mm
Operating Temperature	0˚C to 50˚C (32˚F to 122˚F)
Storage Temperature	-40˚C to 70˚C (-40˚F to 158˚F)
Operating Humidity	10% to 90% RH non-condensing
Storage Humidity	5% to 90% RH non-condensing
Package Content	Media Converter FC111B-20; Power Adapter; Installation Guide

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-tp-link-network-fc111b-20.html