TP-Link ISM321A-20

1000Base-BX WDM Bi-Directional Industrial SFP Module · Specification summary



Standards and Protocols	IEEE 802.3z,TCP/IP
Wave Length	Tx: 1550 nm; Rx: 1310 nm
Power Supply	3.3V
Fiber Type	9/125 µm; Single-mode
Max. Cable Length	20 km
Data Rate	1.25 Gbps
Connector	LC Simplex
Regulatory Compliance	FCC, CE
Environment	Operating Temperature: -40˚C~ 85˚C (-40˚C~ 185˚F); Storage Temperature: -40℃~85℃ (-40˚C~ 185˚F); Operating Humidity: 5%~85% non-condensing; Storage Humidity: 5%~85% non-condensing
Hardware Features (supported)	DDM, SFP-MSA, Hot Swappable
Dimensions (W × D × H)	2.2*0.5* 0.4 in (56.4*13.4*11.0 mm)
Package Content	ISM321LA-20; Installation Guide

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-tp-link-network-ism321a-20.html