TP-Link TL-SG108E

8-Port Gigabit Easy Smart Switch · Specification summary



Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1q, IEEE 802.1p
Interface	8 10/100/1000 Mbps RJ45 Ports; AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m); 100BASE-TX: UTP category 5, 5e cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m); 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m)
Fan Quantity	Fanless
Power Supply	External Power Adapter(Output: 5 VDC/ 0.6 A)
Dimensions (W × D × H)	6.2 × 4.0 × 1.0 in (158 × 101 × 25 mm)
Max. Power Consumption	3.68 W (220 V/ 50 Hz)
Max. Heat Dissipation	12.55 BTU/h
Packet Buffer Memory	1.5 Mb
Jumbo Frame	16 KB
Switching Capacity	16 Gbps
Packet Forwarding Rate	11.9 Mpps
MAC Address Table	4 K
Quality of Service	Support Port-based/802.1p/DSCP priority; Support 4 priority queues; Rate Limit; Storm Control
L2 Features	IGMP Snooping V1/V2/V3; Static Link Aggregation; Port Mirroring; Cable Diagnostics; Loop Prevention
VLAN	Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs); MTU/Port/Tag VLAN
Transmission Method	Store-And-Forward
Certification	FCC, CE
Package Content	TL-SG108E; Power Adapter; Installation Guide; Rubber Feet
Environment	Operating Temperature: 0℃~40℃ (32℉~104℉); Storage Temperature: -40℃~70℃ (-40℉~158℉); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing

Specifications are summarised from the manufacturer's published information (checked 2026-11-02). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-tp-link-network-tl-sg108e.html