



Yealink SIP-T57W

· Specification summary

Display	7-inch adjustable capacitive touch screen, 800 × 480 pixels.
SIP account reference	Up to 16 VoIP accounts; PBX licensing and provisioning require confirmation.
Ethernet	Two Gigabit Ethernet ports. This does not establish PoE output to another device.
PoE reference	IEEE 802.3af is listed. The cited sheet does not specify the PoE class; confirm the supplied unit.
External power option	Optional Yealink adapter: 5 V DC / 2 A output; confirm local plug and package.
Wireless reference	Built-in Bluetooth 4.2 and dual-band 2.4/5 GHz Wi-Fi (802.11a/b/g/n/ac), as documented; confirm the supplied version.
USB interface	One USB 2.0 port; recording needs a flash drive and compatible configuration.
Expansion option	EXP50: up to 3 modules in the cited configuration; accessories and firmware require confirmation.
DECT option	DD10K dongle required: up to 4 handsets and 4 concurrent calls in the cited configuration.

Specifications are summarised from the manufacturer's published information (checked 2026-10-14). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-yealink-sip-phone-sip-t57w.html>