



Yeastar S412

· Specification summary

Device class	VoIP PBX
Fixed FXS ports	8 fixed FXS ports; these are not the four fixed ports of S412 Lite.
Module slots	4 module slots with dedicated internal-extension and external-line roles.
Internal-extension slots	2 slots for internal extensions, S2 Module only.
External-line slots	2 slots for external lines, O2 / BRI / 3G/4G Module only.
Maximum concurrent calls	8 concurrent calls; not the same metric as user capacity.
Maximum FXS ports	12 FXS ports with appropriate configuration; not twelve included extension modules.
Maximum FXO / BRI ports	4 FXO/BRI ports, depending on the selected module mix; not four of each simultaneously.
Cellular interface ceiling	Up to 2 3G/4G interfaces depending on module, operator, network and configuration.
4G data-port ceiling	Up to 1 4G data port in the S412 document column; module/carrier support still needs checking.
VoIP trunks	4 VoIP trunks in the S412 reference column; not four included paid carrier services.
Signalling protocols	SIP (RFC3261) and IAX2; confirm the required trunk configuration.
Transport references	UDP, TCP, TLS and SRTP are listed; this is not a current security or interoperability guarantee.
Codec references	G.711 A/μ-law, G.722, G.726, G.729A, GSM, Speex, ADPCM, iLBC, H.263, H.263P, H.264 and MPEG4; exact endpoint/firmware negotiation still applies.
DTMF references	In-band, RFC4733, RFC2833 and SIP INFO
Ethernet interfaces	2 × 10/100 Mbps Ethernet interfaces; separate from S50 Gigabit interfaces.
IP service references	Static IP, DHCP, VPN, firewall, VLAN, DDNS, PPPoE, QoS, static NAT and STUN; deployment needs its own configuration and security review.
Voicemail reference	5,000 minutes, expandable in the document; storage, media and configuration are not confirmed.
External recording storage	TF card reference; card and usable capacity require separate confirmation.
Power input reference	12 V DC, 3.33 A supply reference for S412; not a mains AC input or measured consumption.
Dimensions reference	29 × 18 × 3.3 cm (L × W × H) in the S412 table; allow separate installed cable clearance.
Weight reference	0.68 kg in the S412 table; package and fitted accessories not confirmed.
Operating temperature	0–40 °C
Storage temperature	–20–65 °C; not the operating-temperature range.

Humidity reference	10–90%, non-condensing
Mounting reference	Desktop or wall-mount reference; bracket, fasteners and local installation are not included.
Ethernet modes	Single (LAN uplink, WAN disabled), Bridge (WAN bridges a PC), or Dual (both ports for uplink).
Application and licence selection	The datasheet marks Linkus Cloud Service, Billing and Hotel features as extra-licence items; confirm current model/firmware/service eligibility before ordering.

Specifications are summarised from the manufacturer's published information (checked 2026-10-20). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · <https://www.isdsb.com.my/product-yeastar-sip-pbx-s412.html>