



ZKTeco C3-200 Plus Package B

Two-door Four-way Controller · Specification summary



Authentication method	Card/Password/QR Code
Power input	Input AC240V, Output DC 12V 4+1A
Operating temperature	0°C to 45°C
Operating humidity	20%~80% RH (non-condensing)
Key features	Including Metal box and PSU(AC Adapter Unit); 4*RS-485 Readers (ZKTeco R5-485 /OSDP),4*26/34/66-bit Wiegand Readers; 100,000 user capacity; 100,000 (1:N) (Standard) card capacity; 100,000 (Static QR Code / Dynamic QR Code) capacity; 500,000 (Standard) transaction capacity; TCP/IP *1 RS-485:ZKTeco RS-485/OSDP *1 Wiegand (nput)*4 USB: Type A (USB Drive Only)*1 Aux Inputs "2, Aux Outputs *2, Electric Lock*2,Door Sensor*2,Exit Button*2, Alarm*2; ZKBio CVAccess for management; Support installation of 1x 7AH SLA Battery

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-zkteco-door-access-c3-200-plus-package-b.html>