



ZKTeco SenseFace 2A/ID/WIFI

SenseFace 2A Face Recognition Terminal – EM(ID) – WiFi ·
Specification summary



Fast biometric performance	<0.35 s face, <0.5 s fingerprint
Managed via software	ZKBio CVAcess / ZKBioTime and mobile/cloud with ZKBio Zlink
Power input	DC 12 V / 1.5 A, adapter do not include
Operating temperature	-5°C to 45°C
Key features	2.4-inch TFT color screen, 1 MP WDR binocular camera, supports face, fingerprint, card (ID/optional IC), and PIN; 1,500 faces, 3,000 fingerprints, 3,000 cards, 3,000 users, 150,000 Transaction Capacity; Communication via TCP/IP, USB; optional Wi-Fi; supports electric lock, door sensor, exit button; Supports Access Control & Time Attendance, photo capture, schedule bell, tamper alarm, multiple authentication modes, SIP Client, ONVIF compatible; Wall-mount installation (Asian Gang Box / Single Gang Box compatible)

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-zkteco-door-access-senseface-2a-id-wifi.html>