



ZKTeco SenseFace 4A/ID/WIFI

SenseFace 4A Face Recognition Terminal – EM(ID) – WiFi ·
Specification summary



Fast biometric performance	<0.35 s facial authentication
Managed via software	ZKBio CVAccess / ZKBioTime; mobile & cloud supported through ZKBio Zlink
Power input	DC 12 V / 3 A, adapter do not include
Operating temperature	-5°C to 45°C; humidity 10%–90% RH (non-condensing)
Key features	4.3-inch TFT color touch screen (272×480), 1 MP WDR binocular camera, supports face, card (ID / optional IC), and PIN; 6,000 faces, 8,000 fingerprints, 8,000 cards, 8,000 users, 200,000 Transaction Capacity; Touchless face recognition distance: 30 cm – 200 cm; Communication via TCP/IP, USB; optional Wi-Fi; supports electric lock, door sensor, exit button, RS485, and Wiegand; Supports Access Control & Time Attendance, photo capture, event photo, schedule bell, tamper alarm, multiple authentication modes, SIP Client (v2.0), ONVIF compatible; IP65-rated waterproof & dustproof design; Wall-mount installation (Asian Gang Box / Single Gang Box compatible)

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak ·

<https://www.isdsb.com.my/product-zkteco-door-access-senseface-4a-id-wifi.html>