ZKTeco SenseFace 7A/MF/WIFI

SenseFace 7A Face Recognition Terminal – Mifare (IC) – WiFi · Specification summary

Fast biometric performance	<0.35 s facial authentication
Managed via software	ZKBio CVAccess / ZKBioTime; mobile & cloud supported through ZKBio Zlink
Power input	DC 12 V / 3 A, adapter do not include
Operating temperature	-5°C to 45°C; humidity 10%–90% RH (non-condensing)
Key features	7-inch TFT color touch screen, 1 MP WDR binocular camera, supports face, card (mifare), and PIN; 10,000 faces, 10,000 fingerprints, 50,000 cards, 50,000 users, 300,000 Transaction Capacity; Touchless face recognition distance: 30 cm – 200 cm; Communication via TCP/IP, USB; optional Wi-Fi; supports electric lock, door sensor, exit button, RS485, and Wiegand; Supports Access Control & Time Attendance, photo capture, event photo, schedule bell, tamper alarm, multiple authentication modes, SIP Client (v2.0), ONVIF compatible; IP65-rated waterproof & dustproof design; Wall-mount installation (Asian Gang Box / Single Gang Box compatible)

Specifications are summarised from the manufacturer's published information (checked 2026-10-26). They describe the cited version only. Confirm the exact model, suffix and supplied revision before ordering. ISD confirms supply, price, availability and warranty separately.

IS Distributions Sdn. Bhd., Kuching, Sarawak · https://www.isdsb.com.my/product-zkteco-door-access-senseface-7a-mf-wifi.html